

DesignLights Consortium



Model Number	SU-WP-120W[Blank;BL;WH]-40/50/57K-G5
Classification	Premium
Primary Use	Outdoor Full-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	116.3 W
Reported Light Output	17855 lm
Reported CCT	4000 K
Reported CRI (Ra)	83
Product ID	S-YCR5DX
DLC Family Code	UUUWBX
Listing Status	Listed
Date Qualified	2025-09-30

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-YCR5DX
Manufacturer	NETWORK LIGHTING CONTROL INC
Brand	SAMARAUSA
Model Number	SU-WP-120W[Blank;BL;WH]-40/50/57K-G5
Parent	Yes
Classification	Premium
DLC Family Code	UUUWBX
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	High Output
Primary Use Designation	Outdoor Full-Cutoff Wall-Mounted Area Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	17855 lm
Reported Efficacy (AC)	153.5 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	83
Reported R9	9
Reported IES Rf	83
Reported IES Rg	97
Reported IES Rcs,h1	-12
Reported Minimum Light Output	9212 lm
Reported Maximum Light Output	17855 lm

Reported Minimum CCT	4000 K
Reported Maximum CCT	5700 K
Reported Default Light Output	17855 lm
Reported BUG Rating	B3 U0 G3

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	116.3 W
Reported Total Harmonic Distortion	9.6 %
Reported Power Factor	0.949
Reported Minimum Input Wattage	60 W
Reported Maximum Input Wattage	116.3
Reported Default Input Wattage	116.3 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	17855 lm
Tested Efficacy (AC)	153.5 lm/W
Tested CCT	3966 K
Tested CRI (Ra)	83
Tested R9	9
Tested IES Rf	83
Tested IES Rg	97
Tested IES Rcs,h1	-12 %
Tested Duv	-0.0005
Field Adjustable Light Distribution Setting	No restriction
Tested BUG Rating	B3 U0 G3

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	116.32 W
Tested Total Harmonic Distortion	9.6 %
Tested Power Factor	0.949

VERSION HISTORY VIEW DETAILS

2025-09-30	Listed	5.1	Premium
------------	--------	-----	---------

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number