

DesignLights Consortium



Model Number	SU-SB-150W-TCP[Blank;(PIR);(PTC);(MS);(PIP);(MSP);(PR);(PSC);(BT)]-G1
Classification	Premium
Primary Use	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
Reported Input Wattage	150.6 W
Reported Light Output	26285 lm
Reported CCT	4000 K
Reported CRI (Ra)	73
Product ID	S-W6QHMD
DLC Family Code	LLLCQV
Listing Status	Listed
Date Qualified	2025-10-06

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-W6QHMD
Manufacturer	NETWORK LIGHTING CONTROL INC
Brand	SAMARAUSA
Model Number	SU-SB-150W-TCP[Blank;(PIR);(PTC);(MS);(PIP);(MSP);(PR);(PSC);(BT)]-G1
Parent	Yes
Classification	Premium
DLC Family Code	LLLCQV

Input Power Type	AC
------------------	----

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	High Output
Primary Use Designation	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	Exterior Photocell, Sensor Receptacle, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	Bluetooth
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	26285 lm
Reported Efficacy (AC)	174.54 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	73
Reported R9	-30
Reported IES Rf	75
Reported IES Rg	94

Reported IES Rcs,h1	-18
Reported Minimum Light Output	11900 lm
Reported Maximum Light Output	26285 lm
Reported Minimum CCT	4000 K
Reported Maximum CCT	5700 K
Reported Default Light Output	26285 lm
Reported BUG Rating	B4 U3 G4

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	150.6 W
Reported Total Harmonic Distortion	9.7 %
Reported Power Factor	0.944
Reported Minimum Input Wattage	70 W
Reported Maximum Input Wattage	150.6
Reported Default Input Wattage	150.6 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	26285 lm
Tested Efficacy (AC)	174.54 lm/W
Tested CCT	3973 K
Tested CRI (Ra)	73
Tested R9	-30
Tested IES Rf	75
Tested IES Rg	94
Tested IES Rcs,h1	-17 %
Tested Duv	0.0002
Field Adjustable Light Distribution Setting	straight down
Tested BUG Rating	B4 U3 G4

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	150.6 W
Tested Total Harmonic Distortion	9.7 %
Tested Power Factor	0.944

VERSION HISTORY VIEW DETAILS

2025-10-14	Listed	5.1	Premium
------------	--------	-----	---------

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number