


DESCRIPTION

Ultra slim design, lamp thickness only 0.39".
 Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K.
 IC rated for direct contact with insulation.
 Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms.



BASED ON SAMPLE SETTING. ACTUAL LUMENS MAY VARY

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
SU-DN3IN-6W5C-G1	3inch	6W	2700K	430lm
			3000K	460lm
			3500K	480lm
			4000K	500lm
			5000K	470lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
SU-DN4IN-9W5C-G1	4inch	9W	2700K	650lm
			3000K	750lm
			3500K	750lm
			4000K	760lm
			5000K	680lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
SU-DN6IN-12W5C-G1	6inch	12W	2700K	850lm
			3000K	930lm
			3500K	990lm
			4000K	1010lm
			5000K	950lm

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
SU-DN6IN-15W5C-G1	6inch	15W	2700K	1200lm
			3000K	1290lm
			3500K	1350lm
			4000K	1360lm
			5000K	1340lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
SU-SP8IN-18WTR5CT-G1	8inch	18W	2700K	1300lm
			3000K	1430lm
			3500K	1570lm
			4000K	1570lm
			5000K	1440lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
SU-DN12IN-24W5C-G1	12inch	24W	2700K	1870lm
			3000K	1950lm
			3500K	2010lm
			4000K	2010lm
			5000K	1900lm

TECHNICAL SPECIFICATION

VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K 3000K 3500K 4000K 5000K
CRI	90
BEAM ANGLE	120°
MATERIAL	PS+AL
COLOR	White
LIFESPAN	≥ 50,000hours
OPERATING TEMP	(-4°F ~ 113°F) -20 ~ 45 °C
DIMMABLE	Triac Dimming
RATING	Suitable for Wet Locations
WARRANTY	5 year limited

FEATURES

- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many Triac Dimmers
- Instant on

INSTALLATION

No existing recessed housing or junction box required.
 Suitable for most new constructions.
 Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.
 Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

LISTING

ETL Listed. Energy Star. FCC. Title24.



Catalog Number : Project Name : Note : Date : Type :

Easily flip the switch for desired CCT

Products view


SIZE & DIMENSION & HOLE CUTOUT

Size	Dimension			Hole Cutout
3inch				
4inch				
6inch				
8inch				
12inch				

RECOMMENDED DIMMER


LUTRON				LEVITON	
TG-600PR-WH	TGCL-153PH-LA	SCL-153PH-WH	MSCL-OP153M	6672	
S-600PR-WH	SLV-600P-AL	DVCL-153P	MACL-153M//MA-R	6674	RNL06
CTCL-153PDH-WH	DV-600PR-WH		PD-6WCL	DSL06	IPL06

ACCESSORIES


J-Box driver



Connector



Hole cutout card

Specification subject to change without notice